



SNC-RS44P

Internal PTZ Dome camera, utilising state-of-the-art images enhancement and XDNR noise reduction.

NEW FEATURE RICH PTZ DOME FROM SONY

Designed for internal use, the SNC-RS44P PTZ dome camera delivers excellent picture quality at D1 Resolution. This level of clarity combined with state-of-the-art image processing and a high speed panning capability make the RS44P one of the most effective CCTV cameras on the market. With a total tilt range of 210° and a 360° endless high-speed panning capability, it can cover a wide monitoring area quickly and in a high level of detail. This capability makes it an obvious choice for mission critical CCTV applications including airport/border and traffic surveillance.

Installation and servicing time is reduced by a newly developed base, with a Quick Release Mechanism, which means the camera can be installed or detached quickly. HPoE (High Power over Ethernet) capability and support for multiple codecs provides ultimate flexibility for system design, integration and installation.

SNC-RS Series Cameras also feature ONVIF (Open Network Video Interface Forum) compliance for easy interoperability with IP monitoring products from a variety of manufacturers.

1 Year PrimeSupport is included as standard within the EU, Norway and Switzerland. This gives users access to an expert helpdesk and, in the unlikely event of a failure, will arrange for an advance replacement unit to be delivered within a target time of one working day. An additional 2 years support is also available as an option.

Features

Improved performance in challenging lighting conditions

Sony's Visibility Enhancer technology improves performance in challenging lighting conditions, for example high-contrast environments, such as casinos and highways that had previously been difficult to monitor. The Visibility Enhancer's advanced system suppresses extreme whites and boosts dark areas in a scene simultaneously and dynamically, to produce clearer images on the screen.

Clear low-light images

XDNR (Excellent Dynamic Noise Reduction) technology virtually eliminates image blur in low-light conditions, enabling users to clearly capture images that have not been easy to portray in the past. It also overcomes the problems associated with many competitor camera models. What's more, when both XDNR and Visibility Enhancer are turned on, the cameras can achieve four times the sensitivity compared to when they are off. This technology is ideal for any outdoor surveillance monitoring, such as in a car park at night.

Powerful optical zoom

18x optical zoom delivers greater flexibility in finding and tracking targets. 12x digital zoom capability providing a total zoom ratio of 216x

Wider vertical viewing range

A 210° tilt angle allows a wider vertical viewing range, whilst 400°/sec pan/tilt speed and 360° continuous rotation allows users to find and track

targets quickly and easily. The E-flip feature provides seamless viewing.

High Power over Ethernet capability (IEEE802.3at)

Supporting high Power over Ethernet (hPoE), the SNC-RS Series can be powered using the same Ethernet cable it uses for data transfer. This feature greatly reduces the physical infrastructure costs and speed of deployment. (Available with version 1.2 or later software.)

Triple Codec Network Operation

This multi-codec camera supports three compression formats: JPEG, the best choice of high-quality still images; MPEG-4, the format that provides clear moving images efficiently over limited-bandwidth networks; and H.264, the alternative for severely limited-bandwidth networks, providing twice the efficiency of MPEG-4. The camera can generate JPEG and MPEG-4 images simultaneously

ONVIF Compliant

The ONVIF (Open Network Video Interface Forum) defines a common protocol for the exchange of information between network video devices including automatic device discovery, video streaming and intelligence metadata. Allows interoperability between network video devices.

Tamper Alarm

When an attempt is made to tamper with the camera, such as spray-painting the lens, the SNC-RS Series detects this and triggers an alarm. This event can also be used to activate the camera relays, or even to start the Voice Alert function.

Advanced Audio Detection

Unlike conventional audio detection where an alarm is triggered based on a preset audio level, the SNC-RS Series triggers its alarms based on ambient sound conditions as the threshold. The camera stores and updates ambient audio levels and frequencies, and when the threshold level based on this data, is surpassed, an alarm is triggered. (Available with version 1.1 or later software.)

Audio Message Alert

The camera can store up to three pre-recorded audio alert messages which may be played via an active speaker upon manual or automatic initiation.

Audio Echo Cancellation

This feature removes the echo frequently encountered between the operator and remote site audio systems when speakers and microphones are used.

Support for IPv6

The SNC-RS Series supports Internet Protocol Version 6 (IPv6).

Local Storage / Wireless Capability

The SNC-RS Series has a Compact Flash (CF) slot. This can be used either with a CF memory card for local video storage, or for wireless capability. The SNCA-CFW5 (802.11b/g) CF type wireless LAN card is supported.

Benefits

Capture Everything

Sony's PTZ network dome cameras deliver clear and crisp CCTV images with a level of detail never seen before. In combination with advanced image processing technology, the SNC-RS44P provides enhanced levels of security even under the most challenging lighting conditions. It also provides the option to cover more area with fewer cameras, depending upon your operational requirements.

Enhanced viewing range

An extended tilt range provides greater viewing flexibility, especially when viewing in zoom.

Simple to install, easy to maintain

The camera can be installed or detached quickly and easily thanks to its newly developed base, which greatly reduces installation and servicing time and costs.

High flexible network capability

Enjoy extraordinary operational flexibility using the ideal compression format for differing image and network types (JPEG for high-quality still images; MPEG-4 and H.264 for clear, moving images over bandwidth-limited networks).

ONVIF compliance offers the optimum in system flexibility.

Compliance with ONVIF (Open Network Video Interface Forum) ensures interoperability and

maximum flexibility between a wide range of manufacturers' network video products.

Technical Specifications

Camera

Image device	1/4-type CCD with Exwave HAD technology
Minimum Illumination	Day: 0.4 lx (XDNR ON VE ON Slow Shutter OFF 50 IRE IP) 0.7 lx (Slow Shutter OFF 50 IRE Analog Video Output) Night: 0.08 lx (XDNR ON VE ON Slow Shutter OFF 50 IRE IP) 0.15 lx (Slow Shutter OFF 50 IRE Analog Video Output)
Number of effective pixels (H x V)	440,000 (752 x 582)
Electronic shutter speed	1 to 1/10,000 s
Auto gain control	Auto/Manual (-3 to +28 dB)
Exposure control	Auto, Full auto, Shutter-priority, Iris-priority, Manual, EV compensation, Backlight compensation
White balance mode	Auto, Indoor, Outdoor, One-push WB, ATW, Manual
Lens type	Auto-focus zoom lens
Zoom ratio	18x
Horizontal viewing angle	2.8 to 48.0 degrees
Focal length	f=4.1 to 73.8 mm
F-number	F1.4 (wide), F3.0 (tele)
Minimum object distance	290 mm (11 1/2 inches) (wide) to 800 mm (31 1/2 inches) (tele)
Pan angle	360 degrees endless rotation
Pan speed	400 degrees/s (max.)
Tilt angle	210 degrees (with e-flip)
Tilt speed	400 degrees/s (max.)

Camera Features

Day/Night *1	YES
Wide-D*2	YES
Visibility Enhancer	YES
XDNR	YES

Image

Codec image size (H x V)	720x480 (NTSC), 720x576 (PAL), 640x480 (VGA), 384x288, 320x240 (QVGA)
Video compression format	H.264, MPEG-4, JPEG
Maximum frame rate	H264/MPEG-4/JPEG: 25 fps (720 x 576)

Audio

Audio compression	G.711/G.726
-------------------	-------------

Scene analytics

Intelligent motion detection	YES (with built-in Post Filter)
Intelligent object detection	NO
Advanced audio detection	YES*3

Network

Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client/server), SMTP, DHCP, DNS, NTP, RTP/RTCP, RTSP, SNMP (MIB-2)
Wireless network	YES (with optional *4)
Number of clients	10
Authentication	IEEE802.1X

Analog video output

Signal system	PAL
Horizontal resolution	530 TVL
S/N ratio	more than 50 dB

Interface

Ethernet	10BASE-T/100BASE-TX (RJ-45)
Serial interface	RS-232C, RS-422/RS-485 (PELCO D protocol)
Card slots	CF card x1
Analog video output	Composite video (1Vp-p)
Sensor input	x 4
Alarm output	x 2
External microphone input	Mini-jack (Monaural), MIC IN/LINE IN: 2.2k ohm, 2.45VDC plug-in power
Audio line output Mini-jack	(Monaural), Max output level: 1 Vrms

General

Mass	Approx. 2.0 kg (4 lb 6 oz)
Dimensions	154 x 226 mm (6 1/8 x 9 inches)
Power requirements	hPoE*5, AC24V, DC12V
Power consumption	23 W Max
Operating temperature	0 to 50 °C
Storage temperature	-20 to +60 °

System requirements

Operating system	Windows XP, Windows Vista
Processor	CPU: Pentium4 3GHz, Intel Core2 Duo 2GHz or higher
Memory	1GB or more
Web browser	Microsoft Internet Explorer Ver6.0 or, Ver7.0